

Characteristics

- Mono-phase
- Compact design
- Extra volume model
- Extra heat capacity

Models

- ELLIPS1 – 2.50m length
- ELLIPS2 – 2.50 m length

Application

- ELLIPS1 up to 2.50m door height
- ELLIPS2 up to 3.00m door height
- Shops and supermarkets
- Entrance of office buildings
- Public buildings

Options

- RAL colour
- Stainless steel
- In-built frost protection, solenoid valve, mini bag filter
- Heating (water, 60/40)
- Heating (water, tailor-made adapted to your water temperature)

Steering

- Integrated intelligent steering panel



Masterveil Europe*

Brusselbaan 192, BE-9320 Erembodegem

Tel: +32 (0)53 60 78 90 | Fax: +32 (0)53 60 78 99 | Mail: office@deweerdtdt.be

* Masterveil is a subsidiary of Deweerdt BVBA

Automation: PLX

Standard features

- . *In-built control panel with high/low speed, delay timers, etc.*
- . *Connector for door contact 24V*
- . *Temperature sensor for heating regulation*
- . *In-built zone valve*
- . *In-built frost protection*
- . *Night heating*
- . *Can be controlled by BMS*

Zone valve: SF20-2

The valve is mounted on the line for return water. The valve closes without pressure.

Frost protection: CO4C

The frost protection is internally mounted and electrically connected on the terminals inside the air curtain.

The sensor is mounted on the return water line. When too low a temperature is detected, the fans shut off and the valve is opened. An alarm is activated.

Mini bag filter for efficient and long life filtering

Conical shaped outblow for real air guidance

Masterveil Europe*

Brusselbaan 192, BE-9320 Erembodegem

Tel: +32 (0)53 60 78 90 | Fax: +32 (0)53 60 78 99 | Mail: office@deweerdtd.be

* Masterveil is a subsidiary of Deweerdt BVBA