

AS K

| Nom | Flux d' air m ³ /h | Effet kW | Air entrée °C | Air sortie °C | H2O entrée °C | H2O sortie °C | P chute H2O kPa | H2O courant l/s | Connexion DN |
|--------|----------------------------------|----------|---------------|---------------|---------------|---------------|-----------------|-----------------|--------------|
| AS 40K | 5000 | 42 | 15 | 40 | 60 | 40 | 9,7 | 0,52 | DN25 |
| AS 40K | 5000 | 37 | 15 | 37 | 60 | 35 | 5,2 | 0,36 | DN25 |
| AS 40K | 5000 | 31 | 15 | 33 | 60 | 30 | 2,8 | 0,25 | DN25 |
| AS 40K | 5000 | 40 | 15 | 39 | 55 | 40 | 14,8 | 0,65 | DN25 |
| AS 40K | 5000 | 35 | 15 | 36 | 55 | 35 | 7 | 0,43 | DN25 |
| AS 40K | 5000 | 30 | 15 | 32 | 55 | 30 | 3,5 | 0,29 | DN25 |
| S 40K | 5000 | 33 | 15 | 35 | 50 | 35 | 10,7 | 0,54 | DN25 |
| AS 40K | 5000 | 28 | 15 | 31 | 50 | 30 | 4,7 | 0,34 | DN25 |
| AS 40K | 5000 | 31 | 15 | 34 | 45 | 35 | 19,5 | 0,75 | DN25 |
| AS 40K | 5000 | 26 | 15 | 31 | 45 | 30 | 7 | 0,42 | DN25 |
| AS 40K | 5000 | 24 | 15 | 29 | 40 | 30 | 12,8 | 0,58 | DN25 |
| AS 40K | 5000 | 19 | 15 | 26 | 40 | 25 | 4 | 0,3 | DN25 |
| | | | | | | | | | |
| AS 45K | 6000 | 52 | 15 | 41 | 60 | 40 | 12,9 | 0,63 | DN25 |
| AS 45K | 6000 | 46 | 15 | 38 | 60 | 35 | 6,9 | 0,44 | DN25 |
| AS 45K | 6000 | 39 | 15 | 34 | 60 | 30 | 3,8 | 0,31 | DN25 |
| AS 45K | 6000 | 48 | 15 | 39 | 55 | 40 | 19,5 | 0,79 | DN25 |
| AS 45K | 6000 | 43 | 15 | 36 | 55 | 35 | 9,4 | 0,52 | DN25 |
| AS 45K | 6000 | 36 | 15 | 33 | 55 | 30 | 4,8 | 0,35 | DN25 |
| AS 45K | 6000 | 40 | 15 | 35 | 50 | 35 | 14,2 | 0,65 | DN25 |
| AS 45K | 6000 | 34 | 15 | 32 | 50 | 30 | 6,4 | 0,41 | DN25 |
| AS 45K | 6000 | 38 | 15 | 34 | 45 | 35 | 26 | 0,91 | DN25 |
| AS 45K | 6000 | 32 | 15 | 31 | 45 | 30 | 9,4 | 0,51 | DN25 |

| | | | | | | | | | |
|---------------|------|----|----|----|----|----|------|------|------|
| AS 45K | 6000 | 29 | 15 | 29 | 40 | 30 | 16,9 | 0,71 | DN25 |
| AS 45K | 6000 | 23 | 15 | 26 | 40 | 25 | 5,35 | 0,37 | DN25 |
| | | | | | | | | | |
| AS 50K | 7000 | 62 | 15 | 42 | 60 | 40 | 16,9 | 0,76 | DN25 |
| AS 50K | 7000 | 56 | 15 | 38 | 60 | 35 | 9,3 | 0,54 | DN25 |
| AS 50K | 7000 | 48 | 15 | 35 | 60 | 30 | 5,1 | 0,38 | DN25 |
| AS 50K | 7000 | 58 | 15 | 40 | 55 | 40 | 25,6 | 0,95 | DN25 |
| AS 50K | 7000 | 52 | 15 | 37 | 55 | 35 | 12,5 | 0,63 | DN25 |
| AS 50K | 7000 | 44 | 15 | 34 | 55 | 30 | 6,4 | 0,43 | DN25 |
| AS 50K | 7000 | 49 | 15 | 36 | 50 | 35 | 18,7 | 0,79 | DN25 |
| AS 50K | 7000 | 42 | 15 | 33 | 50 | 30 | 8,5 | 0,5 | DN25 |
| AS 50K | 7000 | 45 | 15 | 34 | 45 | 35 | 34 | 1,1 | DN25 |
| AS 50K | 7000 | 39 | 15 | 32 | 45 | 30 | 12,5 | 0,62 | DN25 |
| AS 50K | 7000 | 35 | 15 | 30 | 40 | 30 | 22,3 | 0,85 | DN25 |
| AS 50K | 7000 | 28 | 15 | 27 | 40 | 25 | 7,3 | 0,45 | DN25 |



Sous réserve d'erreurs typographiques et de modifications techniques